

Window film and glass compatibility table



INTERIOR WINDOW FILM SERIES		SINGLE PANE	DUAL PANE	DUAL PANE LOW-E	TRIPEL PANE LOW-E
SI	05	●	●	●	■
	15	●	●	●	■
	20	●	●	●	■
	30	●	●	●	■
	35	●	●	●	■
	50	●	●	●	▲
	15 Bronze	●	●	■	▲
	15 Blue	●	●	■	▲
	15 Green	●	●	■	▲
	15 Gold	●	●	■	▲
P	35	●	●	●	■
	40	●	●	●	■
	50	●	●	●	●
	60	●	●	●	●
	70	●	●	●	●
	75	●	●	●	●
N	20	●	●	■	▲
	35	●	■	■	▲
	50	●	●	■	▲
DR	05	●	●	●	■
	15	●	●	●	■
SB	20	●	●	■	▲
	35	●	■	■	▲
S	2	●	●	●	●
	4	●	●	●	●
	4 AG	●	●	●	●
	7	●	●	●	●
	12	●	●	●	●
	12	●	●	●	●
SSI	420	●	●	●	■
	430	●	●	●	■
	820	●	●	●	■
SDR	635	●	●	■	▲
	650	●	●	■	▲
BLKOUT	-	■	▲	▲	▲
WHTOUT	-	●	●	●	■

EXTERIOR WINDOW FILM SERIES		SINGLE PANE	DUAL PANE	DUAL PANE LOW-E	TRIPEL PANE LOW-E
XT	14S	●	●	●	●
	17S	●	●	●	●
	30S	●	●	●	●
	33S	●	●	●	●
	48S	●	●	●	■
	15SSL	●	●	●	●
	08DR	●	●	●	●
	19DR	●	●	●	●
	36DR	●	●	■	■
	20N	●	●	●	■
	40N	●	●	●	■
	47CV	●	●	●	■
	50CV	●	●	●	●
	67CV	●	●	●	●
	70CV	●	●	■	▲
	78CV	●	●	■	■

LEGEND

● Compatible: the window film should not cause any issues with the given glazing system, if installed on a completely intact glass panel, keeping all relevant installation protocols.

■ Conditionally compatible: installation is recommended with safety only on tempered glass. By all means the following aspects must be taken into consideration: size if the glass panel (risks increase over 4 sqm), its angle, orientation and partial shading (both artificial and natural), shading devices (appropriate ventilation), laminated or wire-glass, altitude, orientation of cooling devices, etc.

▲ Not compatible: it is prohibited to install this film on the given glazing system. Edge sealing: in case of all exterior window films and the interior P series, edges must be sealed.